



Machine Tools

USED Haas SL20

CNC Lathe - Slant Bed

£12,500

Stock No. 2010608101U

Machine Specifications

Swing over front apron	584mm
Swing over cross slide	241mm
Maximum machining diameter	262mm
Maximum turning length	508mm
Spindle nose	A2-6
Hole through spindle	76mm
Maximum spindle speed	4000rpm
Spindle motor power	14.9kW
Accessories	Haas CNC Control System Hydraulic 3 jaw chuck Hydraulic tailstock Tool presetter Swarf conveyor Parts catcher Interlocked guarding Auto lubrication Coolant system




HAAS**MODEL**

SL-20TCE

HAAS AUTOMATION, INC, OXNARD, CA. 93030

SERIAL NUMBER

65122

DATE OF MFG

05 02

CE

VOLTAGE 360 / 480

PHASE 3

HERTZ 50 / 60

FULL LOAD 40 AMPS

LARGEST LOAD 30 AMPS

SHORT CIRCUIT

INTERRUPTING CAPACITY - 10,000 AMPS

WIRING DIAGRAM

96

8700

OVER CURRENT PROTECTION PROVIDED
AT MACHINE SUPPLY TERMINALS.**WARNING**LETHAL VOLTAGES INSIDE CABINET!
DISCONNECT FROM POWER SOURCE
BEFORE OPENING CABINET!
TRAINED SERVICE PERSONNEL ONLY!**MADE IN U.S.A.**

P/N 29-7900E







ATTEN



CAUTION: LAY OF SPIN
REDUCE CLAMPING FORCE AND
CAUTION: MINIMUM CLAMPING IS

CHUCK MAINTENANCE

LUBRICATION REQUIREMENTS:
LUBRICATE THE CHUCK WITH OIL
OR GREASE AT THE FOLLOWING
POINTS: CHUCK, CHUCK KEY, CHUCK
KEY KEYWAY, CHUCK KEY KEYWAY
AND CHUCK KEY KEYWAY.

LUBRICATION TYPE:
LUBRICATE WITH OIL OR GREASE.

MAINTENANCE REQUIREMENTS:
LUBRICATE THE CHUCK WITH OIL
OR GREASE AT THE FOLLOWING
POINTS: CHUCK, CHUCK KEY, CHUCK
KEY KEYWAY, CHUCK KEY KEYWAY
AND CHUCK KEY KEYWAY.

WARNING



Warning: Falling objects can
cause injury or death.



Warning: Moving parts can
cause injury or death.



Warning: Pinch points can
cause injury or death.



Warning: Sharp edges can
cause injury or death.



Warning: Hot surfaces can
cause injury or death.